

Nieuwe Kanaal 9F, 6709 PA WAGENINGEN, THE NETHERLANDS Telephone: +31 (0)317 45 34 25 E: mail@skh.nl | **W**: www.skh.nl



# KOMO<sup>®</sup> product certificate PLYWOOD

 Number:
 32621/25

 Issued:
 01-04-2025

 Supersedes:
 32621/23

Producer Joubert Les Eliots S.A.S. 106 Rue des Epinées Les Éliots - Auge-St-Médard F-16170 VAL-D'AUGE FRANCE Tel. +33 5 45 21 62 23 E-mail: joubert@joubert-group.com Website: http://www.joubert-group.com

# **Declaration of SKH**

This product certificate is based upon AD 1705 'Plywood' dd. 09-11-2021 including amendment sheet dd. 04-11-2024, issued by SKH, in conformity with the SKH Regulations for Certification.

The quality system and product characteristics of this product are checked periodically.

# On this basis, SKH declares that there is justified confidence that:

The product delivered by the certificate holder upon delivery complies with:

- The technical specification laid down in this product certificate;

- The product requirements laid down in this product certificate and in the AD;

Provided that the product and the delivery document bear the KOMO<sup>®</sup> mark in a manner indicated in this product certificate.

The essential characteristics, as stipulated in the applicable harmonised European standard, and the corresponding control of the quality system of these characteristics are not part of this declaration.

DOW

For SKH

drs. H.J.O. van Doorn, director

Furthermore, this product certificate is included in the overview on the website of the KOMO foundation: www.komo.nl and www.komo-online.nl.

Users of this product certificate are advised to verify whether this certificate is still valid; consult the SKH-website: www.skh.nl.

This product certificate consists of 4 pages.



The following has been assessed: • quality system • product Periodic control

 Page
 2 of 4

 Number:
 32621/25

 Issued:
 01-04-2025

## 1

# **TECHNICAL SPECIFICATION**

This product certificate applies to the plywood supplied by the producer as specified below and the associated product characteristics and performances.

### Description of different types of panels

Туре	Thicknesses in mm	KOMO class	Wood species	Glue type	Intended application
Joubert Aludoor	40/54	2	Okoumé	PF	In construction
Joubert Aludoor Primed	6-40	3	Okoumé	PF	In construction
Joubert Aludoor Paint	40/54	2	Okoumé	PF	In construction
Joubert Ecopaint	8-40	3	Okoumé	PF	In construction
Joubert Garant	4-45	2	Okoumé	PF	In construction
Joubert Paint Garant	8-40	2	Okoumé	PF	In construction
Joubert Poply	9-40	4	Okoumé	PF	In construction
Joubert Primed	6-40	3	Okoumé	PF	In construction
Joubert Poprimed	9-40	4	Okoumé	PF	In construction
Okouplex	4-45	3	Okoumé	PF	In construction
Sapelli Marine II/II	4-40	2	Sapelli face veneers, Okoumé core	PF	In construction

# Specific characteristics of the different types of plywood

Туре	Overlaid*	Primer*	Prepaint*	Composite	Composite
		(AD 0814)	(AD 0817)	plywood	material
Joubert Aludoor	No	No	No	Yes	Aluminum
Joubert Aludoor Primed	No	No	No	Yes	Aluminum
Joubert Aludoor Paint	Yes	No	No	Yes	Aluminum
Joubert Ecopaint	No	No	No	No	N.a.
Joubert Garant	No	No	No	No	N.a.
Joubert Paint Garant	Yes	No	No	No	N.a.
Joubert Poply	No	No	No	No	N.a.
Joubert Primed	No	No	No	No	N.a.
Joubert Poprimed	No	No	No	No	N.a.
Okouplex	No	No	No	No	N.a.
Sapelli Marine	No	No	No	No	N.a.

\* overlays and coatings on the plywood are only part of this product certificate if the plywood is marked in accordance with paragraph 2 and if the product is listed as such in the table above.

Note: The harmonised European standard NEN-EN 13986 applies to plywood for applications in construction.

Page 3 of 4 Number: 32621/25 Issued: 01-04-2025

2

# MARKS AND INDICATIONS ON THE PRODUCTS AND DELIVERY DOCUMENTS

Each panel of plywood must be marked with the KOMO®-image mark or KOMO®-word mark followed by the certificate number 32621. The execution of the KOMO®-image mark/KOMO®-word mark shall comply with the requirements as included in the document 'Reglement KOMO-merk gebruik door certificaathouders' published by KOMO, whereby the execution is as follows:



Location of the mark: clearly visible on each panel of plywood supplied.

- And is followed by: Number KOMO<sup>®</sup> product certificate.
- Nominal thickness in mm.
- Production date/batch.
- Product class according to AD 1705 table 2.
- If the plywood is provided with a finishing coat by the plywood producer, the letter 'P' must be added to the indication of product class (AD 1705 paragraph 4.4).
- If an overlay is applied to the plywood by the plywood producer, the letter 'O' must be added to the indication of product class (AD 1705 paragraph 4.5).

#### 3 **PRODUCT FEATURES**

### Essential characteristics for the Construction Products Regulation 3.1

The harmonised European standard NEN-EN 13986 applies to plywood for applications in construction. The characteristics listed in the table below are covered by the harmonised part of this standard.

Feature	Determination method	Requirement AD
Release of formaldehyde	NEN-EN 13986+A1 section 5.7	Class E1
Reaction to fire	NEN-EN 13986+A1 section 5.8 or NEN-EN 13501-1	At least D-s2, d0

It was found that the product characteristics listed above meet the limits listed above. The statements above may not be used to replace the CE marking and/or the associated mandatory Declaration of Performance.

#### 3.2 Other product characteristics

The plywood for applications in construction complies with the product requirements laid down in AD 1705 'Plywood'. The table below shows the values of the product characteristics that form part of this product certificate. These comply with the values specified in the table.

Feature	Determination method	Requirement AD	Value
Panel thickness and dimensional deviations	AD 1705 section 4.2, NEN-EN 315	NEN-EN 315	Complies
Composition	AD 1705 section 4.3	Crosswise and symmetrical	According to Table A
Overlay (optional)	AD 1705 section 4.5, PS1-09	PS1-09	- Film - White - 290 g/m <sup>2</sup>
Composite plywood (optional)	AD 1705 section 4.7, NEN-EN 314-2	AD 1705 section 4.7 to be specified by certificate holder	Aludoor: 2 layers aluminum 0.3 mm
Surface finish	AD 1705 section 4.8	AD 1705 section 4.8	Complies
Appearance and permitted defects	AD 1705 section 4.9, NEN-EN 635-2, NEN-EN 635-3	AD 1705 tables 3, 4 and 5	Complies
Gaps and open defects	AD 1705 section 4.10	AD 1705 table 6	Complies
Overlaps	AD 1705 section 4.11	AD 1705 table 7	Complies

 Page
 4 of 4

 Number:
 32621/25

 Issued:
 01-04-2025

# Table A Structure of the panels

Type of panel	Thickness in mm	Number of layers (minimum)
	4 - 5	3
	6	4
	6	5 (for Joubert Garant)
All types	7 - 10	5
	12 - 15	7
	16 - 22	9
	24 - 28	11
	27 - 30	13
	35 - 40	17

# 4 PROCESSING INSTRUCTIONS

The performance of the plywood as stated in this product certificate can only be fulfilled when working in accordance with the processing instructions of the producer of the plywood with the date 10.2020 For the certified processing instructions please consult the SKH website: http://www.skh.nl.

# 5 SUGGESTIONS FOR THE CUSTOMER

# 5.1 On delivery of the products listed under 'technical specification', check that:

- delivered is what was agreed;
- the KOMO® mark and method of marking is correct;
- the products have no visible defects (e.g. due to transport).

No verification of the correctness of the performance of the essential characteristics shall take place under this product certificate. The statements in this product certificate may not be used to replace the CE marking and/or the associated mandatory Declaration of Performance.

If the products are rejected on the basis of the above, contact shall be made with: Joubert Les Eliots S.A.S. and if desirable the certification-body SKH.

# 5.2 Product certificate

It is the duty of the producer to make sure that the buyer receives a copy of the complete product certificate.

# 5.3 Transport and storage

Carry out storage, transport and processing in accordance with the certificate holder's processing instructions included in this product certificate.

# 5.4 Application conditions and processing instructions

Observe the application conditions and processing instructions as included in this product certificate and documents of the certificate holder.

### 5.5 Period of validity

Consult the SKH-website: www.skh.nl to verify whether the product certificate is still valid.





 Number:
 32622/25

 Issued:
 01-04-2025

 Supersedes:
 32622/23

Producer

Joubert St-Jean d'Angély S.A.S. Rue Lafaurie – B.P 106 F-17416 ST. JEAN D'ANGÉLY CEDEX FRANCE Tel. +33 54 63 22 037 E-mail: joubert@joubert-group.com Website: http://www.joubert-group.com

# **Declaration of SKH**

This product certificate is based upon AD 1705 'Plywood' dd. 09-11-2021 including amendment sheet dd. 04-11-2024, issued by SKH, in conformity with the SKH Regulations for Certification.

The quality system and product characteristics of this product are checked periodically.

# On this basis, SKH declares that there is justified confidence that:

- The product delivered by the certificate holder upon delivery complies with:
- The technical specification laid down in this product certificate;

- The product requirements laid down in this product certificate and in the AD;

Provided that the product and the delivery document bear the KOMO<sup>®</sup> mark in a manner indicated in this product certificate.

The essential characteristics, as stipulated in the applicable harmonised European standard, and the corresponding control of the quality system of these characteristics are not part of this declaration.

OOW

For SKH

drs. H.J.O. van Doorn, director

Furthermore, this product certificate is included in the overview on the website of the KOMO foundation: www.komo.nl and www.komo-online.nl.

Users of this product certificate are advised to verify whether this certificate is still valid; consult the SKH-website: www.skh.nl.

This product certificate consists of 4 pages.



The following has been assessed: • quality system • product Periodic control

 Page
 2 of 4

 Number:
 32622/25

 Issued:
 01-04-2025

# 1

# **TECHNICAL SPECIFICATION**

This product certificate applies to the plywood supplied by the producer as specified below and the associated product characteristics and performances.

### Description of different types of panels

Туре	Thicknesses in mm	KOMO class	Wood species	Glue type	Intended application
Joubert Aludoor	40/54	2	Okoumé	PF	In construction
Joubert Aludoor Primed	6-40	3	Okoumé	PF	In construction
Joubert Aludoor Paint	40/54	2	Okoumé	PF	In construction
Joubert Ecopaint	8-40	3	Okoumé	PF	In construction
Joubert Garant	4-45	2	Okoumé	PF	In construction
Joubert Paint Garant	8-40	2	Okoumé	PF	In construction
Joubert Poply	9-40	4	Okoumé	PF	In construction
Joubert Primed	6-40	3	Okoumé	PF	In construction
Joubert Poprimed	9-40	4	Okoumé	PF	In construction
Okouplex	4-45	3	Okoumé	PF	In construction
Sapelli Marine II/II	4-40	2	Sapelli face veneers, Okoumé core	PF	In construction

# Specific characteristics of the different types of plywood

Туре	Overlaid*	Primer* (AD 0814)	Prepaint* (AD 0817)	Composite	Composite material
			1	plywood	
Joubert Aludoor	No	No	No	Yes	Aluminum
Joubert Aludoor Primed	No	No	No	Yes	Aluminum
Joubert Aludoor Paint	Yes	No	No	Yes	Aluminum
Joubert Ecopaint	No	No	No	No	N.a.
Joubert Garant	No	No	No	No	N.a.
Joubert Paint Garant	Yes	No	No	No	N.a.
Joubert Poply	No	No	No	No	N.a.
Joubert Primed	No	No	No	No	N.a.
Joubert Poprimed	No	No	No	No	N.a.
Okouplex	No	No	No	No	N.a.
Sapelli Marine	No	No	No	No	N.a.

\* overlays and coatings on the plywood are only part of this product certificate if the plywood is marked in accordance with paragraph 2 and if the product is listed as such in the table above.

Note: The harmonised European standard NEN-EN 13986 applies to plywood for applications in construction.

Page 3 of 4 Number: 32622/25 01-04-2025 Issued:

2

# MARKS AND INDICATIONS ON THE PRODUCTS AND DELIVERY DOCUMENTS

Each panel of plywood must be marked with the KOMO®-image mark or KOMO®-word mark followed by the certificate number 32622. The execution of the KOMO®-image mark/KOMO®-word mark shall comply with the requirements as included in the document 'Reglement KOMO-merk gebruik door certificaathouders' published by KOMO, whereby the execution is as follows:



Location of the mark: clearly visible on each panel of plywood supplied.

- And is followed by: Number KOMO<sup>®</sup> product certificate.
- Nominal thickness in mm.
- Production date/batch.
- Product class according to AD 1705 table 2.
- If the plywood is provided with a finishing coat by the plywood producer, the letter 'P' must be added to the indication of product class (AD 1705 paragraph 4.4).
- If an overlay is applied to the plywood by the plywood producer, the letter 'O' must be added to the indication of product class (AD 1705 paragraph 4.5).

#### 3 **PRODUCT FEATURES**

#### 3.1 **Essential characteristics for the Construction Products Regulation**

The harmonised European standard NEN-EN 13986 applies to plywood for applications in construction. The characteristics listed in the table below are covered by the harmonised part of this standard.

Feature	Determination method	Requirement AD
Release of formaldehyde	NEN-EN 13986+A1 section 5.7	Class E1
Reaction to fire	NEN-EN 13986+A1 section 5.8	At least D-s2, d0
	or NEN-EN 13501-1	

It was found that the product characteristics listed above meet the limits listed above. The statements above may not be used to replace the CE marking and/or the associated mandatory Declaration of Performance.

#### 3.2 Other product characteristics

The plywood for applications in construction complies with the product requirements laid down in AD 1705 'Plywood'. The table below shows the values of the product characteristics that form part of this product certificate. These comply with the values specified in the table.

Feature	Determination method	Requirement AD	Value
Panel thickness and	AD 1705 section 4.2,	NEN-EN 315	Complies
dimensional deviations	NEN-EN 315		
Composition	AD 1705 section 4.3	Crosswise and symmetrical	According to Table
			А
Overlay (optional)	AD 1705 section 4.5,	PS1-09	- Film
	PS1-09		- White
			- 290 g/m <sup>2</sup>
Composite plywood	AD 1705 section 4.7,	AD 1705 section 4.7	Aludoor: 2 layers
(optional)	NEN-EN 314-2	to be specified by	aluminum 0.3 mm
		certificate holder	
Surface finish	AD 1705 section 4.8	AD 1705 section 4.8	Complies
Appearance and	AD 1705 section 4.9,	AD 1705 tables 3, 4 and 5	Complies
permitted defects	NEN-EN 635-2,		
	NEN-EN 635-3		
Gaps and open defects	AD 1705 section 4.10	AD 1705 table 6	Complies
Overlaps	AD 1705 section 4.11	AD 1705 table 7	Complies

 Page
 4 of 4

 Number:
 32622/25

 Issued:
 01-04-2025

# Table A Structure of the panels

Type of panel	Thickness in mm	Number of layers (minimum)
	4 - 5	3
	6	4
	6	5 (for Joubert Garant)
All types	7 - 10	5
	12 - 15	7
	16 - 22	9
	24 - 28	11
	27 - 30	13
	35 - 40	17

# 4 PROCESSING INSTRUCTIONS

The performance of the plywood as stated in this product certificate can only be fulfilled when working in accordance with the processing instructions of the producer of the plywood with the date 10.2020 For the certified processing instructions please consult the SKH website: http://www.skh.nl.

# 5 SUGGESTIONS FOR THE CUSTOMER

# 5.1 On delivery of the products listed under 'technical specification', check that:

- delivered is what was agreed;
- the KOMO® mark and method of marking is correct;
- the products have no visible defects (e.g. due to transport).

No verification of the correctness of the performance of the essential characteristics shall take place under this product certificate. The statements in this product certificate may not be used to replace the CE marking and/or the associated mandatory Declaration of Performance.

If the products are rejected on the basis of the above, contact shall be made with: Joubert St-Jean d'Angély S.A.S. and if desirable the certification-body SKH.

### 5.2 Product certificate

It is the duty of the producer to make sure that the buyer receives a copy of the complete product certificate.

# 5.3 Transport and storage

Carry out storage, transport and processing in accordance with the certificate holder's processing instructions included in this product certificate.

# 5.4 Application conditions and processing instructions

Observe the application conditions and processing instructions as included in this product certificate and documents of the certificate holder.

### 5.5 Period of validity

Consult the SKH-website: www.skh.nl to verify whether the product certificate is still valid.