

## OKOUMÉ SÉLECTION



Okoume throughout - Face veneers II/II  
Exterior gluing Class 3 - E1  
NF Extérieur CTB-X certified (for structural use)

Selected interiors.

Exterior joinery: for high quality production and finish, shutters.



## TECHNICAL INFORMATION

### DEFINITION

Okoume throughout plywood with II/II rotary cut face veneers. All the cores are carefully selected.

Choosing Okoumé sélection means:

#### Beauty:

- Choice of splendour.
- Simplified finish: unequalled impregnation qualities: paint, wood stain.
- Material without cracks, no resurfacing of the resin.
- Material resistance over time.

#### Mastering one's budget:

- Easiness of machining: the placing of panels is optimized enabling maximum output.
- Wood output superior to timber: controlled moisture content, a stable material, a constant format, no aspect defects.

### GENERAL INFORMATION

#### Compliance of plywood with European norms:

- Gluing class: according to EN 314-2
- Faces classification: according to EN 635-2
- Dimension tolerance: according to EN 315
- Panel marking: according to EN 636

### SPECIFICATIONS

Thicknesses: 25 to 40 mm.

CE2+ marking for structural use according to EN 13986 (control certificate delivered by FCBA).

Density:	500 kg/m <sup>3</sup> (± 50 kg/m <sup>3</sup> )
Fire reaction:	D-s2, d0*
Formaldehyde emission:	Class E1 US EPA TSCA Title VI - CARB ULEF
Heat conductivity:	$\lambda = 0,13$ W/m.k
Pentachlorophenol content:	< 5 ppm

\* Depending on how the panel is installed.

Thickness mm	Sizes cm
25	250 x 122
30	250 x 153
35	310 x 153
40	

For FSC®-certified panels, depending on availability, contact us.